

Fundamental concepts of processing and image analysis

António J. R. Neves

Electronics, Telecommunications and Informatics Department

University of Aveiro

`an@ua.pt`

`http://sweet.ua.pt/an`

Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing



Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

A picture is worth than 1000 words



A picture is worth than millions words




Human vision (1)

- Vision is a complex physical and intellectual human task that stands as a primary interaction tool with the world.
- It is a complex process not completely understood, even after hundreds of years of research.
- The visualization of a physical process involves an almost simultaneous interaction of the eyes and the brain.
- This interaction is performed by a network of neurons, receptors and other specialized cells.

Human vision (2)


- The human eye is equipped with a variety of optical elements, including the cornea, iris, pupil, a variable lens and the retina.
- Can do amazing things like:
 - Recognize people and objects
 - Navigate through obstacles
 - Understand mood in the scene
 - Imagine stories
- But:
 - Suffers from illusions
 - Ignores many details
 - Ambiguous description of the world
 - Doesn't care about accuracy of world

Illusions (1)




Edward H. Adelson

Illusions (2)





Edward H. Adelson


Illusions (3)



- The human visual system exhibits a considerable cognitive component, influenced by memory, context, and intention:



Which is the longer one?



A triangle?

- **Computer vision** is a field that includes methods for acquiring, processing, analyzing, and understanding images . . .
- Computer vision applications are increasing:
 - surveillance;
 - machine inspection;
 - medicine;
 - robotics;
 - entertainment;
 - media.
- The utopic goal: make computer vision converge towards human vision. **Can we ever accomplish that?**

- Computer vision seeks to develop algorithms that replicate one of the most amazing capabilities of the human brain - inferring properties of the external world purely by means of the light reflected from various objects to the eyes.
- With vision, it is possible to determine how far away objects are, how they are oriented with respect to the subject, and in relationship to various other objects.
- It is possible to guess their colors and textures and recognize them.
- It is possible to segment regions of space corresponding to particular objects and track them over time.
- In this course, we will study some of the concepts and algorithms used in Computer Vision to achieve the referred tasks . . .

Topics in computer vision


- Image acquisition and representation
 - digital cameras, digital images, color spaces, . . .
- Digital camera calibration
 - intrinsic parameters, distortion correction, color calibration, . . .
- Low-level image processing
 - neighbors, filtering, histograms, contours, morphological operators . . .
- Stereo image processing
 - camera calibration, 3D reconstruction, . . .
- 3D imaging
 - 3D cameras, point clouds, . . .
- Video processing
 - egomotion, tracking, optical flow, . . .
- High-level image processing
 - template matching, pattern recognition, descriptors, . . .

- Making Things See, Greg Borenstein, O'Reilly 2012
- Learning OpenCV: Computer Vision in C++ with the OpenCV Library, Gary Bradski, Adrian Kaehler, O'Reilly 2012
- Machine vision: Theory, algorithms, practicalities, E. R. Davies, Morgan Kaufmann 2005.
- Digital Image Processing, Rafael C. Gonzalez, Richard E. Woods, Prentice Hall, 2007
- Image Processing: Analysis and Machine Vision, Milan Sonka et al., Chapman & Hall, 2007

Contents


- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

History of cameras (1544)



Camera Obscura, Gemma Frisius, 1544

History of cameras (1568)



Lens Based Camera Obscura, 1568

History of cameras (1837)



Still Life, Louis Jaques Mande Daguerre, 1837

History of cameras (1930)





History of cameras (1970 - nowadays)



Silicon Image Detector, 1970 - digital cameras

Human eye



Pinhole Camera Model





Figure 1.2. The pinhole imaging model.

Image through a lens



- All the rays of light that came from an object in direction to the lens converge, on the other side, in another point at a certain distance from the lens. This distance is called **focal distance**.
- f smaller – wide-angle camera; f gets larger – more telescopic.
- All the points that verify this fact are denoted the **focal plane**.
- There are some other important parameters related to lens: Field of View, Depth of Field, . . .


Basic Camera Geometry


- Far objects appear smaller.
- Lines project to lines.
- Lines in 3D project to lines in 2D.
- Distances and angles are not preserved.
- These geometric properties are “common sense”. Other properties can be inferred if we formalize the model using . . . Mathematics, of course. . .

Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras**
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing



- Image acquisition using a digital camera:
(IEEE SP Magazine, Jan 2005)





- Some considerations: speed, resolution, cost, signal/noise ratio, . . .
- **CCD - charge coupled device** - Higher dynamic range, High uniformity, Lower noise.
- **CMOS - Complementary Metal Oxide Semiconductor** - Lower voltage, Higher speed, Lower system complexity.

The Bayer matrix



Digital cameras - several solutions



- Several interfaces (Firewire, GigE, CameraLink, USB, ...).
- Scientific usage (high resolution, long exposure time, ...).
- High speed (ex. 1000 fps).
- Linear (ex. 10000 lines per second).
- 3D
- Infrared (ex. 8 to 14 μm).
- High dynamic range (ex. using a prism and two sensors).
- Multispectral


Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images**
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

Sampling and quantization

- Generally, an image can be represented by a two-dimensional function, $f(x, y)$, where x and y are spatial coordinates.
- The meaning of f in a given point in space, (x, y) , depends on the source that generated the image (visible light, x-rays, ultrasound, radar, ...).
- Nevertheless, we generally assume that $f(x, y) \geq 0$.
- Moreover, both the spatial coordinates and the function values are continuous quantities.
- Therefore, to convert $f(x, y)$ into a digital image, it is necessary to perform **spatial sampling** and **amplitude quantization**.


Digitalization: sampling + quantization



Sampling and quantization





- Sampling and quantization — example:

(Gonzalez & Woods)




Sampling and quantization

- Sampling and quantization — example:
(Gonzalez & Woods)



- Typically, a **digital image** is represented by a rectangular matrix of scalars or vectors.



- The $f(i,j)$ are named *pixels* and, usually, $f(i,j) \in \mathcal{I} \subset \mathbb{N}_0^n$.

- We will consider digital images of the following types:

- Black and white (binary images).

$$f(i, j) \in \{0, 1\}$$

- Grayscale images.

$$f(i, j) \in \{0, 1, \dots, 2^b - 1\}$$

- Color-indexed images.

$$f(i, j) \in \{0, 1, \dots, 2^b - 1\} \xrightarrow{\alpha} \mathcal{I} \subset \{0, 1, \dots, 2^{b'} - 1\}^3$$

- Color images (for example, RGB images).

$$f(i, j) \in \{0, 1, \dots, 2^b - 1\}^3$$

Examples



Color



Color-indexed (256)



Grayscale (256)



Black and white

Color-indexed images

- Usually, images having a reduced set of colors are represented using a matrix of indexes (the index image) and a color table.



=



Index image

+

	R	G	B
0	100	035	203
1	030	025	200
2	167	205	010
3	132	219	045
...			

Color table

Infrared and depth images ...



An Infrared image (Gobi Camera)



A Depth image (Kinect sensor)


Stereo vision




Left



Right



Rectified image



Depth image

Contents


- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing**
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

- A video signal can be represented by a 3D-function, $v(x, y, t)$, where x and y are spatial coordinates and t denotes time.
- The process of converting analog video into digital video requires both **spatial and temporal sampling**, besides **amplitude quantization**.
- Therefore, a **digital video** is a temporal sequence of digital images which we represent by $v(i, j, k)$, with $k = t/T, k \in \mathbb{N}_0$.
- $T \in \mathbb{R}$ indicates the period of time between two consecutive images (we call them frames). Therefore, $1/T$ (Hz) is the frame rate.
- Sometimes we will refer to video **fields**. They occur in interlaced video and are made of the even (odd) lines of a frame.

- Several information can be extracted from time varying sequences of images:
 - Camouflaged objects are only easily seen when they move
 - The relative sizes and position of objects are more easily determined when the objects move
 - Even simple image differencing provides an edge detector for the silhouettes of texture-free objects moving over any static background.

- The analysis of visual motion can be divided into two stages:
 - the measurement of the motion
 - the use of motion data to segment the scene into distinct objects and to extract three dimensional information about the shape and motion of the objects.
- There are two types of motion to consider:
 - movement in the scene with a static camera,
 - and movement of the camera, or ego motion.
- Since motion is relative, these types of motion should be the same. However, this is not always the case, since if the scene moves relative to the illumination, shadow and specularities effects need to be dealt with.


- The motion field is the projection of the 3D scene motion into the image.



- Definition: optical flow is the apparent motion of brightness patterns (or colors) in the image.
- Ideally, optical flow would be the same as the motion field.
- Have to be careful: apparent motion can be caused by lighting changes without any actual motion.
- To estimate pixel motion from image we have to solve the pixel correspondence problem.
- Given a pixel in frame t , look for nearby pixels with same characteristics (color, brightness, ...) in frame $t - 1$.

Background subtraction

- It is possible to look at video data as a spatio-temporal volume.
- If camera is stationary, each line through time corresponds to a single ray in space.



- Background subtraction is a commonly used class of techniques for segmenting out objects of interest in a scene for applications such as:
 - Surveillance
 - Robot vision
 - Object tracking
 - Traffic applications
 - Human motion capture
 - Augmented reality

Background subtraction

- It involves comparing an observed image with an estimate of the image if it contained no objects of interest.
- The areas of the image plane where there is a significant difference between the observed and estimated images indicate the location of the objects of interest.
- The name background subtraction comes from the simple technique of subtracting the observed image from the estimated image and thresholding the result to generate the objects of interest.

Important issues

- foreground detection – how the object areas are distinguished from the background;
- background maintenance – how the background is maintained over time;
- post-processing – how the segmented object areas are postprocessed to reject false positives.



Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces**
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

The visible spectrum



Spectral colors (pure colors)


Cor	Wavelength
Violet	≈ 380–440 nm
Blue	≈ 440–485 nm
Cyan	≈ 485–500 nm
Green	≈ 500–565 nm
Yellow	≈ 565–590 nm
Orange	≈ 590–625 nm
Red	≈ 625–740 nm

The human perception of color

- Normally, the characteristics that allow colors to be distinguished are:
 - The **brightness** (how bright is the color).
 - The **hue** (the dominant color).
 - The **saturation** (how pure is the color).
- Together, the hue and the saturation define the **chromaticity**.
- Therefore, a color can be characterized by the brightness and the chromaticity.


The human perception of color

- The human eye has **photoreceptors** that are sensitive to short wavelengths (*S*), medium wavelengths (*M*) and long wavelengths (*L*), also known as the blue, green and red photoreceptors.



Additive primaries


- The red, green and blue are the three additive primary colors.




- Adding these three colors produces white.

The *RGB* color space

- Besides the use in acquisition on digital cameras, for example, the displays have pigments of these three colors...



21" TV CRT Display



17" PC CRT Display

The *CMY* color space

- The *CMY* color space is based on the subtractive properties of inks.
- The cyan, magenta and yellow are the subtractive primaries. They are the complements, respectively, of the red, green and blue. For example, the cyan subtracts the red from the white.



- Conversion from *RGB* to *CMY*: $C = 1 - R$, $M = 1 - G$, $Y = 1 - B$.

The CMY color space



C component




M component



Y component

The CMYK color space

- Due to technological difficulties regarding the reproduction of black, the **CMYK** color space is generally used for printing.



C component



M component





Y component



K component

The *HLS* and *HSV* color spaces

- The **HSL** and **HSV** are the two most common cylindrical coordinate representations of colors.
- They rearrange the geometry of RGB colors in an attempt to be more intuitive and perceptually relevant than the cartesian (cube) representation.
- They were developed in the 1970s for computer graphics applications, and are used for color pickers, in color-modification tools in image editing software, and commonly for image analysis and computer vision.



- RGB to HSV:

$$V = \max(R, G, B)$$

$$S = \begin{cases} \frac{V - \min R, G, B}{V} & \text{if } V \neq 0 \\ 0 & \text{otherwise} \end{cases}$$

$$H = \begin{cases} 60(G - B)/S & \text{if } V = R \\ 120 + 60(B - R)/S & \text{if } V = G \\ 240 + 60(R - G)/S & \text{if } V = B \end{cases}$$

The *HLS* and *HSV* color spaces

- RGB to HSL:

$$V_{max} = \max R, G, B$$


$$V_{min} = \min R, G, B$$

$$L = \frac{V_{max} + V_{min}}{2}$$

$$S = \begin{cases} \frac{V_{max} - V_{min}}{V_{max} + V_{min}} & \text{if } L < 0.5 \\ \frac{V_{max} - V_{min}}{2 - (V_{max} + V_{min})} & \text{if } L \geq 0.5 \end{cases}$$

$$H = \begin{cases} 60(G - B)/S & \text{if } V_{max} = R \\ 120 + 60(B - R)/S & \text{if } V_{max} = G \\ 240 + 60(R - G)/S & \text{if } V_{max} = B \end{cases}$$

The *HLS* and *HSV* color spaces




H component



S component



V component



H component



S component



L component

The *YUV* color space

- The *YUV* color space is used in some television standards.
- *Y* is the luminance component:

$$Y = 0.299R + 0.587G + 0.114B$$


- Components *U* and *V* represent the chrominance:

$$U = -0.147R - 0.289G + 0.436B = 0.492(B - Y)$$
$$V = 0.615R - 0.515G - 0.100B = 0.877(R - Y)$$

- For $R, G, B \in [0, 1]$, we have $Y \in [0, 1]$,
 $U \in [-0.436, 0.436]$ and $V \in [-0.615, 0.615]$.

The YUV color space

- $U - V$ plane, for a constant value of Y , equal to 0.5:



Advantages of the YUV color space

- The YUV color space allowed to maintain the compatibility with the old “black and white” television receivers.
- The human eye is more sensitive to the green color, which is represented mainly by the Y component.
- The U and V components are related to the blue and red.
- Since the human eye is less sensitive to the blue and red, it is possible to reduce the bandwidth used to represent the U and V components, without introducing significant perceptual degradation.

The $YCbCr$ color space

- This is usually designated the digital version of YUV .
- The JPEG standard, as well as some other MPEG video standards, allows all 256 values in an 8 bits per component representation.
- In this case, considering $R, G, B \in \{0, \dots, 255\}$, we have:

$$Y = 0.299R + 0.587G + 0.114B$$

$$C_b = 128 - 0.168736R - 0.331264G + 0.5B$$

$$C_r = 128 + 0.5R - 0.418688G - 0.081312B$$

- After the conversion, $Y, C_b, C_r \in \{0, \dots, 255\}$.
- Besides its use in image and video coding, this color space is also used in some computer vision applications.


The $YCbCr$ color space



Y component



C_b component



C_r component


Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration**
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing


- In order to use a digital camera in some applications, it is necessary to calibrate some parameters.
- Colormetric parameters: the parameters that are related to color and intensity of the acquired image (gain, white-balance, brightness, sharpness, . . .). The available parameters depends on the image processing pipeline of each camera.
- Extrinsic parameters: the parameters that define the location and orientation of the camera reference frame with respect to a known world reference frame.
- Intrinsic parameters: the parameters necessary to link the pixel coordinates of an image point with the corresponding coordinates in the camera reference frame.

Colormetric parameters (1)

A typical image processing pipeline (inside the image device) for a tri-stimulus system is shown bellow. This processing can be performed on the YUV or RGB components depending on the system. This should be understood as a mere example.



Colormetric parameters (2)



Extrinsic parameters

Extrinsic parameters denote the coordinate system transformations from 3D world coordinates to 3D camera coordinates.

In other words they reflect the projection view of the camera taking into consideration its relative position to the world coordinates (translation operation) and its rotations when we consider the camera coordinate system three axis in relation to the world coordinate system three axis.

To note the **Extrinsic parameters** does not reflect the position of the camera in regard to the world coordinate system. It is, in fact, the position of the origin of the world coordinate system expressed in coordinates of the camera-centered coordinate system.

If \mathbf{R} and \mathbf{T} are the extrinsic parameters, then the position of the camera \mathbf{C} expressed in world coordinates is

$$\mathbf{C} = -\mathbf{R}^{-1}\mathbf{T} = -\mathbf{R}^T\mathbf{T}$$



Intrinsic parameters



Intrinsic parameters are defined as a matrix of the form

$$A = \begin{bmatrix} \alpha_x & \gamma & u_0 \\ 0 & \alpha_y & v_0 \\ 0 & 0 & 1 \end{bmatrix}$$

The intrinsic matrix containing 5 intrinsic parameters. These parameters include focal length, image format, and principal point. The parameters $\alpha_x = f \cdot m_x$ and $\alpha_y = f \cdot m_y$ represent focal length in terms of pixels, where m_x and m_y are the scale factors relating pixels to distance. γ represents the skew coefficient between the x and the y axis, and is normally 0. u_0 and v_0 represent the principal point, which would be ideally in the centre of the image.

Richard Hartley and Andrew Zisserman (2003). Multiple View Geometry in Computer Vision. Cambridge University Press. pp. 155–157. ISBN 0-521-54051-8

Example of intrinsic and extrinsic calibration





Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering**
- 9 Histograms
- 10 Segmentation
- 11 Color image processing

Pixel Neighbours

- Many image processing operations make use of spatial relationships between pixels.
- A number of methods have been devised to specify pixel neighbors and calculate distance.
- The 4-neighbors of a pixel (x,y) are the closest pixels in horizontal and vertical directions (D4).
- The 8-neighbors are the 4-neighbors plus the four closest pixels in diagonal direction (D8).
- Diagonal only (DN).



- A group of pixels is said to be 4-connected if every pixel is 4-connected to the group.

- A group of pixels is said to be 8-connected every pixel is 8-connected to the group.


- The distance between pixels (x,y) and (u,v) can be calculated in several ways:
 - Euclidean (L2): $D = [(x - u)^2 + (y - v)^2]^{1/2}$
 - City-block (L1): $D = |x - u| + |y - v|$
 - Chessboard (Linf): $D = \max(|x - u|, |y - v|)$
- Although Euclidean distance is more accurate, the sqrt makes it expensive to calculate.

- Spatial filters make use of a fixed sized neighborhood in an input image to calculate output intensities.
- Linear filters use a weighted sum of pixels in the input image $f(i, j)$ to calculate the output pixel $g(i, j)$. In most cases, the sum of weights is one, so the output brightness = input brightness.
- Nonlinear filters can not be calculated using just a weighted sum (sqrt, log, sorting, selection).
- We can formalize the phrase “weighted sum of pixels” using correlation and convolution.
- The mathematical model is the discrete convolution operator based on the kernel h :

$$g(i, j) = \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} h(i - m, j - n) f(i, j)$$

Examples of filters (1)

- Average - the easiest spatial filter to implement. The kernel is a matrix with all the values equals to one (the pixel is replaced by an average of the $N \times M$ neighbors). This filter smooths an image and removes noise and small details.
- Binomial - uses Binomial coefficients as weights to give more emphasis to pixels near the center of the $N \times M$ neighborhood.
- Gaussian - uses the Gaussian function to define the neighborhood weights.




Example of filters (2)




Edge detection



Canny






Laplace



Sobel



Hough Transform




Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms**
- 10 Segmentation
- 11 Color image processing

Histograms: definition



- In statistics, a histogram is a graphical display of tabulated frequencies.
- Typically represented as a bar chart.



- In images, allow us to see the color or intensity distribution.
- The collected counts of data can be organized into a set of predefined bins.
- It is also possible to count image features that we want to measure (i.e. gradients, directions, etc).
- Some important parts of an histogram:
 - dims: The number of parameters you want to collect data.
 - bins: The number of subdivisions in each dim.
 - range: The limits for the values to be measured.
- If we want to count two features, the resulting histogram would be a 3D plot (in which x and y would be bin_x and bin_y for each feature and z would be the number of counts for each combination of (bin_x, bin_y)).


Histograms: example (1)

- Example of an histogram obtained from a grayscale image.
- Each bin shows the number of times each one of the gray values are present in the image.



Histograms: example (2)

- Example of an histogram showing the distribution of the colors on an image.



Histograms: operations

- Histogram operations are designed to enhance the visibility of objects of interest in an image.
- Histogram Equalization - improves the contrast in an image, in order to stretch out the intensity range.
- Local Histogram Equalization - increase the amount of enhancement by looking at local intensity properties (dividing an image into regions and perform histogram equalization on each sub-image or using local statistics).
- Histogram Comparison - get a numerical parameter that expresses how well two histograms match each other (ex. Correlation, Chi-Square, Intersection, ...).
- Sum, subtract, ...

Histograms: equalization

- Goal of histogram equalization is to reshape the image histogram to make it flat and wide.
- One of the solutions is to use the cumulative histogram (integral of intensity histogram) as the intensity mapping function.




Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation**
- 11 Color image processing

Segmentation: concept

- Intermediate processing towards object recognition.
- Localize regions with common properties.
- Make a partition over the pixel ensemble.
- Usual grouping properties (Gray level, Color, Texture).
- Often requires preprocessing.
- Segmentation of non-trivial images is a difficult task.
- Segmentation accuracy determines the eventual success/failure of computerized image analysis.

Applications of segmentation



- The basis of many region based segmentation algorithms.
- The most immediate and computationally appealing step.
- Direct image partition based on intensity properties.
- Several approaches:
 - Global Thresholding
 - Variable Thresholding
 - Local - $T(x, y)$ depends on properties of the neighborhood of (x, y) .
 - Adaptive - $T(x, y)$ depends on the spatial coordinates, x and y .
 - The Otsu's method - Optimal global thresholding based on probabilistic estimates obtained from the histogram.

- Region growing is a procedure that groups pixels or subregions into larger regions based on a predefined criteria.
 - Start with a set of "seed" points and from these, grow regions by appending to each seed those neighboring pixels that have properties similar to the seed (intensity, color, ...).
- Selection of seeds
 - Often interactive
 - Automated
- Centroids of pixel clusters
- Additional criteria: size and shape of region grown so far
- Stopping rules
 - Ideally, growing a region should stop when no more pixels satisfy the criteria for inclusion in that region.

Morphological operators




Green channel of the RGB image




Binary image (Otsu method)



Dilation of the binary image



Erosion of the binary image




Difference between dilation and erosion

Contents

- 1 Computer vision
- 2 Image formation
- 3 Digital cameras
- 4 Digital images
- 5 Video Processing
- 6 Color Spaces
- 7 Camera calibration
- 8 Filtering
- 9 Histograms
- 10 Segmentation
- 11 Color image processing



Pseudocolor

- The colors of a pseudocolour image do not attempt to approximate the real colours of the subject.
- Example: The Moon - The color of the map represents the elevation. The highest points are represented in red. The lowest points are represented in purple.





Intensity Slicing

- Quantize pixel intensity to a specific number of values (slices).
- Map one colour to each slice.
- Loss of information.
- Enhanced human visibility.



Intensity to color

- Each color component is calculated using a transformation function.
- Viewed as an Intensity to Colour map.
- Does not need to use RGB space!
- Examples: display thermal or depth images



- Increase or decrease intensity
- Color complements
- Color slicing (define a hyper-volume of interest inside my color space and keep colours if inside the hyper-volume or change the others to a neutral colour).
- Tone and color corrections.
- Histogram equalization.

Hyperspectral images

- Hyperspectral sensors collect information as a set of 'images'.
- Each image represents a range of the electromagnetic spectrum.
- Hyperspectral remote sensing is used in a wide array of applications: agriculture, Mineralogy, Surveillance, physics, etc.





Image compression

- Lossless vs lossy
- Progressive vs sequential
- Video vs still image
- Several standards: MPEG, H26X, JPEG2000, JPEG-LS, PNG, GIF, JPEG...



Example: JPEG compression



Feature detection

