VC 11/12 – T7 Spatial Filters

Mestrado em Ciência de Computadores

Mestrado Integrado em Engenharia de Redes e

Sistemas Informáticos

Miguel Tavares Coimbra



Outline


- Spatial filters
- Frequency domain filtering
- Edge detection

Acknowledgements: Most of this course is based on the excellent courses offered by Prof. Shree Nayar at Columbia University, USA and by Prof. Srinivasa Narasimhan at CMU, USA. Please acknowledge the original source when reusing these slides for academic purposes.

Topic: Spatial filters

- Spatial filters
- Frequency domain filtering
- Edge detection

Images are Discrete and Finite



Convolution

$$g(i,j) = \sum_{m=1}^{M} \sum_{n=1}^{N} f(m,n)h(i-m,j-n)$$

Fourier Transform


$$F(u,v) = \sum_{m=1}^{M} \sum_{n=1}^{N} f(m,n) e^{-i2\pi \left(\frac{mu}{M} + \frac{nv}{N}\right)}$$

Inverse Fourier Transform

$$f(k,l) = \frac{1}{MN} \sum_{u=1}^{M} \sum_{v=1}^{N} F(u,v) e^{i2\pi \left(\frac{ku}{M} + \frac{lv}{N}\right)}$$

Spatial Mask

- Simple way to process an image.
- Mask defines the processing function.
- Corresponds to a multiplication in frequency domain.



Example

- Each mask position has weight w.
- The result of the operation for each pixel is given by:

1	2	1
0	0	0
-1	-2	1

2	2	2
4	4	4
4	5	6

Mask

Image

$$g(x,y) = \sum_{s=-at=-b}^{a} \sum_{s=-at=-b}^{b} w(s,t) f(x+s,y+t)$$
=1*2+2*2+1*2+...
=8+0-20
=-12

Definitions

Spatial filters


- Use a mask (kernel) over an image region.
- Work directly with pixels.
- As opposed to: Frequency filters.

Advantages

- Simple implementation: convolution with the kernel function.
- Different masks offer a large variety of functionalities.

Averaging

Let's think about averaging pixel values



For n=2, convolve pixel values with

Which is faster?
$$(a)O(2(n+1))$$
 $(b)O((n+1)^2)$

2D images:

(a) use 1

1 2 1


then

or (b) use

1 2 1 *

Averaging

The convolution kernel




Repeated averaging ≈ Gaussian smoothing

Gaussian Smoothing

Gaussian kernel

$$h(i,j) = \frac{1}{2\pi\sigma^2} e^{-\frac{1}{2}\left(\frac{i^2+j^2}{\sigma^2}\right)}$$

Filter size $N \propto \sigma$...can be very large (truncate, if necessary)



2D Gaussian is separable!

$$g(i,j) = \frac{1}{2\pi\sigma^2} \sum_{m=1}^{\infty} e^{-\frac{1}{2}\frac{m^2}{\sigma^2}} \sum_{n=1}^{\infty} e^{-\frac{1}{2}\frac{n^2}{\sigma^2}} f(i-m,j-n)$$



N pixels






Gaussian Smoothing


 A Gaussian kernel gives less weight to pixels further from the center of the window

This kernel is an approximation of a Gaussian function:

$$F[x, y]$$

$$h(u, v) = \frac{1}{2\pi\sigma^2} e^{-\frac{u^2 + v^2}{\sigma^2}}$$





Mean Filtering


- We are degrading the energy of the high spatial frequencies of an image (low-pass filtering).
 - Makes the image 'smoother'.
 - Used in noise reduction.
- Can be implemented with spatial masks or in the frequency domain.






1	1	1
1	~	1
1	1	1

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9













Median Filter

- Smoothing is averaging
 - (a) Blurs edges
 - (b) Sensitive to outliers


- Median filtering
 - Sort N^2-1 values around the pixel
 - Select middle value (median)



Non-linear (Cannot be implemented with convolution)



Border Problem



Border Problem

- Ignore
 - Output image will be smaller than original
- Pad with constant values
 - Can introduce substantial 1st order derivative values
- Pad with reflection
 - Can introduce substantial 2nd order derivative values


Topic: Frequency domain filtering

- Spatial filters
- Frequency domain filtering
- Edge detection

Image Processing in the Fourier Domain








Does not look anything like what we have seen

Convolution in the Frequency Domain



Low-pass Filtering


Original image




Low-pass image




FFT of original image



FFT of low-pass image



Low-pass filter



Lets the low frequencies pass and eliminates the high frequencies.

Generates image with overall shading, but not much detail

High-pass Filtering


Original image




High-pass image




FFT of original image



FFT of high-pass image



High-pass filter



Lets through the high frequencies (the detail), but eliminates the low frequencies (the overall shape). It acts like an edge enhancer.

Boosting High Frequencies


Original image




High boosted image



FFT of original image




FFT of high boosted image



High-boost filter





































The Ringing Effect








Topic: Edge detection


- Spatial filters
- Frequency domain filtering
- Edge detection

Edge Detection

- Convert a
 2D image into a set of curves
 - Extractssalientfeatures ofthe scene
 - More compact than pixels





Origin of Edges




Edges are caused by a variety of factors

How can you tell that a pixel is on an edge?






Edge Types



Real Edges



Noisy and Discrete!

We want an **Edge Operator** that produces:


- Edge Magnitude
- Edge Orientation
- High Detection Rate and Good Localization

Gradient

- Gradient equation: $\nabla f = \left[\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}\right]$
- Represents direction of most rapid change in intensity

$$\nabla f = \left[\frac{\partial f}{\partial x}, 0\right]$$


$$\nabla f = \left[0, \frac{\partial f}{\partial y}\right]$$



- Gradient direction: $\theta = \tan^{-1} \left(\frac{\partial f}{\partial y} / \frac{\partial f}{\partial x} \right)$
- The edge strength is given by the gradient magnitude $\|\nabla f\|$

$$\|\nabla f\| = \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$$

Theory of Edge Detection



Unit step function:

$$u(t) = \begin{cases} 1 & \text{for } t > 0 \\ \frac{1}{2} & \text{for } t = 0 \\ 0 & \text{for } t < 0 \end{cases} \qquad u(t) = \int_{-\infty}^{t} \delta(s) ds$$

Image intensity (brightness):

$$I(x,y) = B_1 + (B_2 - B_1)u(x\sin\theta - y\cos\theta + \rho)$$



Theory of Edge Detection

Partial derivatives (gradients):

$$\frac{\partial I}{\partial x} = +\sin\theta (B_2 - B_1)\delta(x\sin\theta - y\cos\theta + \rho)$$

$$\frac{\partial I}{\partial y} = -\cos\theta (B_2 - B_1)\delta(x\sin\theta - y\cos\theta + \rho)$$

Squared gradient:

$$s(x,y) = \left(\frac{\partial I}{\partial x}\right)^2 + \left(\frac{\partial I}{\partial y}\right)^2 = \left[\left(B_2 - B_1\right)\delta(x\sin\theta - y\cos\theta + \rho)\right]^2$$


Edge Magnitude: $\sqrt{s(x,y)}$


Edge Orientation: $\arctan\left(\frac{\partial I}{\partial y} / \frac{\partial I}{\partial x}\right)$ (normal of the edge)


Rotationally symmetric, non-linear operator

Theory of Edge Detection

Laplacian:
$$\nabla^2 I = \frac{\partial^2 I}{\partial x^2} + \frac{\partial^2 I}{\partial y^2} = (B_2 - B_1) \delta'(x \sin \theta - y \cos \theta + \rho)$$
 Rotationally symmetric, linear operator







Discrete Edge Operators

How can we differentiate a *discrete* image?

Finite difference approximations:

$$\begin{split} \frac{\partial I}{\partial x} &\approx \frac{1}{2\varepsilon} \left(\left(I_{i+1,j+1} - I_{i,j+1} \right) + \left(I_{i+1,j} - I_{i,j} \right) \right) & \qquad I_{i,j+1} \quad I_{i+1,j+1} \\ \frac{\partial I}{\partial y} &\approx \frac{1}{2\varepsilon} \left(\left(I_{i+1,j+1} - I_{i+1,j} \right) + \left(I_{i,j+1} - I_{i,j} \right) \right) & \qquad I_{i,j} \quad I_{i+1,j} \end{split}$$

Convolution masks:

$$\frac{\partial I}{\partial x} \approx \frac{1}{2\varepsilon} \begin{vmatrix} -1 & 1 \\ -1 & 1 \end{vmatrix} \qquad \frac{\partial I}{\partial y} \approx \frac{1}{2\varepsilon} \begin{vmatrix} 1 & 1 \\ -1 & -1 \end{vmatrix}$$

$$\frac{\partial I}{\partial y} \approx \frac{1}{2\varepsilon} \begin{vmatrix} 1 & 1 \\ -1 & -1 \end{vmatrix}$$

Discrete Edge Operators

Second order partial derivatives:

Second order partial derivatives:
$$\frac{\partial^2 I}{\partial x^2} \approx \frac{1}{\varepsilon^2} \left(I_{i-1,j} - 2I_{i,j} + I_{i+1,j} \right)$$

$$\frac{\partial^2 I}{\partial y^2} \approx \frac{1}{\varepsilon^2} \left(I_{i,j-1} - 2I_{i,j} + I_{i,j+1} \right)$$

$$I_{i-1,j} \quad I_{i,j} \quad I_{i+1,j}$$

$$I_{i-1,j-1} \quad I_{i,j-1} \quad I_{i+1,j-1}$$

$$egin{array}{c|c} I_{i-1,j+1} & I_{i,j+1} & I_{i+1,j+1} \ \hline I_{i-1,j} & I_{i,j} & I_{i+1,j} \ \hline I_{i-1,j-1} & I_{i,j-1} & I_{i+1,j-1} \end{array}$$

• Laplacian :


$$\nabla^2 I = \frac{\partial^2 I}{\partial x^2} + \frac{\partial^2 I}{\partial y^2}$$

Convolution masks:

(more accurate)

The Sobel Operators

- Better approximations of the gradients exist
 - The Sobel operators below are commonly used



Comparing Edge Operators

Gradient:

$$\nabla f = \left[\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y} \right]$$

Good Localization
Noise Sensitive
Poor Detection

Roberts (2 x 2):

0	1
-1	0

Sobel (3 x 3):


-1	0	1
7	0	1
-1	0	1

1	1	1
0	0	0
1	-1	1

Sobel (5 x 5):

-1	-2	0	2	1
-2	-3	0	3	2
-3	-5	0	5	3
-2	-3	0	3	2
-1	-2	0	2	1


1	2	3	2	1
2	3	5	3	2
0	0	0	0	0
-2	-3	-5	-3	-2
-1	-2	-3	-2	-1



Poor Localization
Less Noise Sensitive
Good Detection


Effects of Noise

- Consider a single row or column of the image
 - Plotting intensity as a function of position gives a signal



Where is the edge??

Solution: Smooth First




Where is the edge?

Look for peaks in
$$\frac{\partial}{\partial x}(h \star f)$$


Derivative Theorem of Convolution

$$\frac{\partial}{\partial x}(h \star f) = (\frac{\partial}{\partial x}h) \star f$$

...saves us one operation.




Laplacian of Gaussian (LoG)



Where is the edge?

Zero-crossings of bottom graph!

2D Gaussian Edge Operators



Gaussian

Laplacian of Gaussian Mexican Hat (Sombrero)

• ∇^2 is the Laplacian operator: $\nabla^2 f = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2}$

Canny Edge Operator

- Smooth image / with 2D Gaussian: G*I
- Find local edge normal directions for each pixel

$$\overline{\mathbf{n}} = \frac{\nabla(G * I)}{|\nabla(G * I)|}$$

Compute edge magnitudes


$$|\nabla(G*I)|$$


 Locate edges by finding zero-crossings along the edge normal directions (non-maximum suppression)

$$\frac{\partial^2 (G * I)}{\partial \overline{\mathbf{n}}^2} = 0$$

Non-maximum Suppression

- Check if pixel is local maximum along gradient direction
 - requires checking interpolated pixels p and r













Canny Edge Operator



- The choice of σ depends on desired behavior
 - large σ detects large scale edges
 - small σ detects fine features

Difference of Gaussians (DoG)


 Laplacian of Gaussian can be approximated by the difference between two different Gaussians



DoG Edge Detection



Unsharp Masking



Resources

Gonzalez & Woods – Chapter 4