

# **MySQL C API**

TABD

# MySQL 8.0 Reference Manual

- <https://dev.mysql.com/doc/refman/8.0/en/>
- <https://dev.mysql.com/doc/refman/8.0/en/installing.html>
- <https://dev.mysql.com/doc/refman/8.0/en/c-api.html>

## 28.6 MySQL C API

### 28.6.3 Building and Running C API Client Programs

```
gcc -c `mysql_config --cflags` progname.c
```

```
gcc -o progname progname.o `mysql_config --libs`
```

## 28.6.4 C API Data Structures

- MySQL

This structure represents handler for one database connection. It is used for almost all MySQL functions.

- MySQL\_RES

This structure represents the result of a query that returns rows ([SELECT](#), [SHOW](#), [DESCRIBE](#), [EXPLAIN](#)).

- MySQL\_ROW

This is a type-safe representation of one row of data. It is currently implemented as an array of counted byte strings. (You cannot treat these as null-terminated strings if field values may contain binary data, because such values may contain null bytes internally.)

## 28.6.4 C API Data Structures

- `MYSQL_FIELD`

This structure contains metadata: information about a field, such as the field's name, type, and size. You may obtain the `MYSQL_FIELD` structures for each field by calling `mysql_fetch_field()` repeatedly. Field values are not part of this structure; they are contained in a `MYSQL_ROW` structure.

- `MYSQL_FIELD_OFFSET`

This is a type-safe representation of an offset into a MySQL field list. (Used by `mysql_field_seek()`.) Offsets are field numbers within a row, beginning at zero.

# MYSQL\_FIELD

The MYSQL\_FIELD structure contains the members described in the following list:

`char * name`

The name of the field, as a null-terminated string. If the field was given an alias with an AS clause, the value of name is the alias. For a procedure parameter, the parameter name.

`char * org_name`

The name of the field, as a null-terminated string. Aliases are ignored. For expressions, the value is an empty string. For a procedure parameter, the parameter name.

`char * table`

The name of the table containing this field, if it is not a calculated field. For calculated fields, the table value is an empty string. If the column is selected from a view, table names the view. If the table or view was given an alias with an AS clause, the value of table is the alias. For a UNION, the value is the empty string. For a procedure parameter, the procedure name.

....

## 28.6.5 C API Function Overview

- <https://dev.mysql.com/doc/refman/8.0/en/c-api-function-overview.html>
- mysql\_init(): Gets or initializes a MYSQL structure.
- mysql\_real\_connect(): Connects to a MySQL server.
- mysql\_real\_query(): Executes an SQL query specified as a counted string.
- mysql\_store\_result(): Retrieves a complete result set to the client.
- mysql\_fetch\_row(): Fetches the next row from the result set.
- ....

# EXAMPLES

```
#include <stdio.h>
#include <mysql.h>

int main(int argc, char **argv)
{
    printf("MySQL client version: %s\n", mysql_get_client_info());

    exit(0);
}
```

Here is how we compile the code example.

```
$ gcc version.c -o version `mysql_config --cflags --libs`
$ ./version
MySQL client version: 5.1.67
```

# EXAMPLES

```
#include <stdio.h>
#include <mysql.h>

int main(int argc, char **argv)
{
    MYSQL *con = mysql_init(NULL);

    if (con == NULL)
    {
        fprintf(stderr, "%s\n", mysql_error(con));
        exit(1);
    }

    if (mysql_real_connect(con, "localhost", "root", "root_pswd",
                           NULL, 0, NULL, 0) == NULL)
    {
        fprintf(stderr, "%s\n", mysql_error(con));
        mysql_close(con);
        exit(1);
    }

    if (mysql_query(con, "CREATE DATABASE testdb"))
    {
        fprintf(stderr, "%s\n", mysql_error(con));
        mysql_close(con);
        exit(1);
    }

    mysql_close(con);
    exit(0);
}
```

# EXAMPLES

```
#include <my_global.h>
#include <mysql.h>

void finish_with_error(MYSQL *con)
{
    fprintf(stderr, "%s\n", mysql_error(con));
    mysql_close(con);
    exit(1);
}

int main(int argc, char **argv)
{
    MYSQL *con = mysql_init(NULL);

    if (con == NULL)
    {
        fprintf(stderr, "%s\n", mysql_error(con));
        exit(1);
    }

    if (mysql_real_connect(con, "localhost", "user12", "34klq*",
                           "testdb", 0, NULL, 0) == NULL)
    {
        finish_with_error(con);
    }

    if (mysql_query(con, "DROP TABLE IF EXISTS Cars")) {
        finish_with_error(con);
    }

    if (mysql_query(con, "CREATE TABLE Cars(Id INT, Name TEXT, Price INT)")) {
        finish_with_error(con);
    }

    if (mysql_query(con, "INSERT INTO Cars VALUES(1,'Audi',52642)")) {
        finish_with_error(con);
    }

    if (mysql_query(con, "INSERT INTO Cars VALUES(2,'Mercedes',57127)")) {
        finish_with_error(con);
    }

    mysql_close(con);
    exit(0);
}
```

# EXAMPLES

```
#include <stdio.h>
#include <mysql.h>

void finish_with_error(MYSQL *con)
{
    fprintf(stderr, "%s\n", mysql_error(con));
    mysql_close(con);
    exit(1);
}

int main(int argc, char **argv)
{
    MYSQL *con = mysql_init(NULL);

    if (con == NULL)
    {
        fprintf(stderr, "mysql_init() failed\n");
        exit(1);
    }

    if (mysql_real_connect(con, "localhost", "user12", "34klq*",
                           "testdb", 0, NULL, 0) == NULL)
    {
        finish_with_error(con);
    }

    if (mysql_query(con, "SELECT * FROM Cars"))
    {
        finish_with_error(con);
    }

    MYSQL_RES *result = mysql_store_result(con);

    if (result == NULL)
    {
        finish_with_error(con);
    }

    int num_fields = mysql_num_fields(result);

    MYSQL_ROW row;

    while ((row = mysql_fetch_row(result)))
    {
        for(int i = 0; i < num_fields; i++)
        {
            printf("%s ", row[i] ? row[i] : "NULL");
        }
        printf("\n");
    }

    mysql_free_result(result);
    mysql_close(con);

    exit(0);
}
```

# TUTORIAL

- <http://zetcode.com/db/mysqlc/>

# EXERCISE

Create a C function that print a result set in a formatted manner, just like the mysql client shell:

Id	Name	Price
1	Audi	52642
2	Mercedes	57127
3	Skoda	9000
4	Volvo	29000
5	Bentley	350000
6	Citroen	21000
7	Hummer	41400
8	Volkswagen	21600