

A "Hands-on" Introduction to OpenMP*

Tim Mattson Principal Engineer Intel Corporation timothy.g.mattson@intel.com Larry Meadows Principal Engineer Intel Corporation lawrence.f.meadows@intel.com

Preliminaries: part 1

Disclosures

- The views expressed in this tutorial are those of the people delivering the tutorial.
 - -We are <u>not</u> speaking for our employers.
 - -We are not speaking for the OpenMP ARB
- This is a new tutorial for us:
 - Help us improve ... tell us how you would make this tutorial better.

Preliminaries: Part 2

Our plan for the day .. Active learning!

- We will mix short lectures with short exercises.
- You will use your laptop for the exercises ... that way you'll have an OpenMP environment to take home so you can keep learning on your own.

Please follow these simple rules

 Do the exercises we assign and then change things around and experiment.

– Embrace active learning!

Don't cheat: Do Not look at the solutions before you complete an exercise ... even if you get really frustrated.

Our Plan for the day

Торіс	Exercise	concepts	
I. OMP Intro	Install sw, hello_world	Parallel regions	
II. Creating threads	Pi_spmd_simple	Parallel, default data environment, runtime library calls	← Break
III. Synchronization	Pi_spmd_final	False sharing, critical, atomic	
IV. Parallel loops	Pi_loop	For, reduction	
V. Odds and ends	No exercise	Single, master, runtime libraries, environment variables, synchronization, etc.	← lunch
VI. Data Environment	Pi_mc	Data environment details, modular software, threadprivate	
VII. Worksharing and schedule	Linked list, matmul	For, schedules, sections	Brook
VIII. Memory model	Producer consumer	Point to point synch with flush	← Break
IX OpenMP 3 and tasks	Linked list	Tasks and other OpenMP 3 features	4

Outline

Introduction to OpenMP • Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks



OpenMP Basic Defs: Solution Stack



OpenMP core syntax

Most of the constructs in OpenMP are compiler directives.

#pragma omp construct [clause [clause]...]

Example

#pragma omp parallel num_threads(4)

- Function prototypes and types in the file: #include <omp.h>
- Most OpenMP* constructs apply to a "structured block".
 - Structured block: a block of one or more statements with one point of entry at the top and one point of exit at the bottom.
 - It's OK to have an exit() within the structured block.

Exercise 1, Part A: Hello world Verify that your environment works Write a program that prints "hello world".

void main()
{

int ID = 0; printf(" hello(%d) ", ID); printf(" world(%d) \n", ID); Exercise 1, Part B: Hello world
Verify that your OpenMP environment works
Write a multithreaded program that prints "hello world".

<pre>#include "omp.h" void main() {</pre>		
#pragma omp parallel	Switches for compiling and linking	
{	-fopenmp gcc -mp pgi	
int $ID = 0;$	/Qopenmp intel	
<pre>printf(" hello(%d) ", ID); printf(" world(%d) \n", ID); }</pre>		

Exercise 1: Solution A multi-threaded "Hello world" program

Write a multithreaded program where each thread prints "hello world".



OpenMP Overview: How do threads interact?

 OpenMP is a multi-threading, shared address model.

Threads communicate by sharing variables.

 Unintended sharing of data causes race conditions:

> race condition: when the program's outcome changes as the threads are scheduled differently.

• To control race conditions:

Use synchronization to protect data conflicts.

Synchronization is expensive so:

 Change how data is accessed to minimize the need for synchronization.

Outline

Introduction to OpenMP • Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

OpenMP Programming Model:

Fork-Join Parallelism:

- Master thread spawns a team of threads as needed.
- Parallelism added incrementally until performance goals are met: i.e. the sequential program evolves into a parallel program.



Thread Creation: Parallel Regions

You create threads in OpenMP* with the parallel construct.

For example, To create a 4 thread Parallel region:

Each thread executes a copy of the code within the structured block Runtime function to request a certain number of threads

int ID = omp_get_thread_num();
pooh(ID,A);

Runtime function returning a thread ID

Each thread calls pooh(ID,A) for ID = 0 to 3

Thread Creation: Parallel Regions

- You create threads in OpenMP* with the parallel construct.
- For example, To create a 4 thread Parallel region:

Each thread executes a copy of the code within the structured block



Each thread calls pooh(ID,A) for ID = 0 to 3

* The name "OpenMP" is the property of the OpenMP Architecture Review Board

Thread Creation: Parallel Regions example



Exercises 2 to 4: Numerical Integration



Mathematically, we know that:

$$\int_{0}^{1} \frac{4.0}{(1+x^{2})} dx = \pi$$

We can approximate the integral as a sum of rectangles:



Where each rectangle has width Δx and height $F(x_i)$ at the middle of interval i.

Exercises 2 to 4: Serial PI Program

static long num_steps = 100000; double step; void main () { int i; double x, pi, sum = 0.0;

step = 1.0/(double) num_steps;

```
for (i=0;i< num_steps; i++){
    x = (i+0.5)*step;
    sum = sum + 4.0/(1.0+x*x);
}
pi = step * sum;</pre>
```

Exercise 2

- Create a parallel version of the pi program using a parallel construct.
- Pay close attention to shared versus private variables.
- In addition to a parallel construct, you will need the runtime library routines
 - oint omp_get_num_threads(); __
 - oint omp_get_thread_num();
 - double omp_get_wtime();



Outline

Introduction to OpenMP • Creating Threads Synchronization Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks



Synchronization: critical

 Mutual exclusion: Only one thread at a time can enter a critical region.

float res;

#pragma omp parallel

float B; int i, id, nthrds;

id = omp_get_thread_num();

Threads wait their turn – only one at a time calls consume() nthrds = omp_get_num_threads();

for(i=id;i<niters;i+nthrds){</pre>

B = big_job(i);

#pragma omp critical consume (B, res);

Synchronization: Atomic

 Atomic provides mutual exclusion but only applies to the update of a memory location (the update of X in the following example)

#pragma omp parallel
{
 double tmp, B;
 B = DOIT();
 tmp = big_ugly(B);
#pragma omp atomic
 X += tmp;

Atomic only protects the read/update of X

Exercise 3

- In exercise 2, you probably used an array to create space for each thread to store its partial sum.
- If array elements happen to share a cache line, this leads to false sharing.
 - Non-shared data in the same cache line so each update invalidates the cache line ... in essence "sloshing independent data" back and forth between threads.
- Modify your "pi program" from exercise 2 to avoid false sharing due to the sum array.

Outline

Introduction to OpenMP • Creating Threads Synchronization 📥 🔸 Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

SPMD vs. worksharing

- A parallel construct by itself creates an SPMD or "Single Program Multiple Data" program ... i.e., each thread redundantly executes the same code.
- How do you split up pathways through the code between threads within a team?
 - This is called worksharing
 - Loop construct
 - Sections/section constructs
 - Single construct

- Task construct Coming in OpenMP 3.0

Discussed later

The loop worksharing Constructs

 The loop workharing construct splits up loop iterations among the threads in a team

```
#pragma omp parallel
```

```
#pragma omp for
for (I=0;I<N;I++){
     NEAT_STUFF(I);
```

Loop construct name: •C/C++: for •Fortran: do

The variable I is made "private" to each thread by default. You could do this explicitly with a "private(I)" clause

Loop worksharing Constructs A motivating example

#pragma omp parallel

for(i=0;I<N;i++) { a[i] = a[i] + b[i];}

OpenMP parallel region

Sequential code

OpenMP narallel

OpenMP parallel region and a worksharing for construct

#pragma omp parallel
#pragma omp for
for(i=0;I<N;i++) { a[i] = a[i] + b[i];}</pre>

int id, i, Nthrds, istart, iend;

istart = id * N / Nthrds;

iend = (id+1) * N / Nthrds;

if (id == Nthrds-1)iend = N;

id = omp_get_thread_num();

Nthrds = omp_get_num_threads();

for(i=istart;I<iend;i++) { a[i] = a[i] + b[i];}

Combined parallel/worksharing construct

 OpenMP shortcut: Put the "parallel" and the worksharing directive on the same line

```
double res[MAX]; int i;
#pragma omp parallel
```

```
#pragma omp for
for (i=0;i< MAX; i++) {
    res[i] = huge();</pre>
```

double res[MAX]; int i;
#pragma omp parallel for
for (i=0;i< MAX; i++) {
 res[i] = huge();</pre>

These are equivalent

Working with loops

Basic approach

- Find compute intensive loops
- Make the loop iterations independent .. So they can safely execute in any order without loop-carried dependencies
- Place the appropriate OpenMP directive and test



Reduction

• How do we handle this case?

```
double ave=0.0, A[MAX]; int i;
for (i=0;i< MAX; i++) {
    ave + = A[i];
}
ave = ave/MAX;
```

- We are combining values into a single accumulation variable (ave) ... there is a true dependence between loop iterations that can't be trivially removed
- This is a very common situation ... it is called a "reduction".
- Support for reduction operations is included in most parallel programming environments.

Reduction

OpenMP reduction clause:

reduction (op : list)

Inside a parallel or a work-sharing construct:

- A local copy of each list variable is made and initialized depending on the "op" (e.g. 0 for "+").
- Compiler finds standard reduction expressions containing "op" and uses them to update the local copy.
- Local copies are reduced into a single value and combined with the original global value.

 The variables in "list" must be shared in the enclosing parallel region.

```
double ave=0.0, A[MAX]; int i;
#pragma omp parallel for reduction (+:ave)
for (i=0;i< MAX; i++) {
    ave + = A[i];
}
ave = ave/MAX;</pre>
```

OpenMP: Reduction operands/initial-values

- Many different associative operands can be used with reduction:
- Initial values are the ones that make sense mathematically.

Operator	Initial value
+	0
*	1
-	0

C/C++ only		
Operator	Initial value	
&	~0	
l	0	
۸	0	
&&	1	
	0	

Fortran Only		
Operator	Initial value	
.AND.	.true.	
.OR.	.false.	
.NEQV.	.false.	
.IEOR.	0	
.IOR.	0	
.IAND.	All bits on	
.EQV.	.true.	
MIN*	Largest pos. number	
MAX*	Most neg. number	

Exercise 4

- Go back to the serial pi program and parallelize it with a loop construct
- Your goal is to minimize the number changes made to the serial program.

Outline

Introduction to OpenMP • Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks
Synchronization: Barrier

Barrier: Each thread waits until all threads arrive.

#pragma omp parallel shared (A, B, C) private(id)
{
 id=omp_get_thread_num();
 A[id] = big_calc1(id);
#pragma omp barrier
#pragma omp for
 for(i=0;i<N;i++){C[i]=big_calc3(i,A);}
#pragma omp for nowait
 for(i=0;i<N;i++){ B[i]=big_calc2(C, i); }
 A[id] = big_calc4(id);</pre>

implicit barrier at the end of a parallel region no implicit barrier due to nowait

Master Construct

- The master construct denotes a structured block that is only executed by the master thread.
- The other threads just skip it (no synchronization is implied).

```
#pragma omp parallel
{
    do_many_things();
#pragma omp master
    { exchange_boundaries(); }
#pragma omp barrier
    do_many_other_things();
```

Single worksharing Construct

- The single construct denotes a block of code that is executed by only one thread (not necessarily the master thread).
- A barrier is implied at the end of the single block (can remove the barrier with a *nowait* clause).

```
#pragma omp parallel
{
    do_many_things();
#pragma omp single
    { exchange_boundaries(); }
    do_many_other_things();
```

Synchronization: ordered

The ordered region executes in the sequential order.

#pragma omp parallel private (tmp)
#pragma omp for ordered reduction(+:res)
for (l=0;l<N;l++){
 tmp = NEAT_STUFF(l);
#pragma ordered
 res += consum(tmp);
}</pre>

Synchronization: Lock routines

Simple Lock routines:

A simple lock is available if it is unset.

-omp_init_lock(), omp_set_lock(), omp_unset_lock(), omp_test_lock(), omp_destroy_lock() A lock implies a memory fence (a "flush") of all thread visible variables

Nested Locks

A nested lock is available if it is unset or if it is set but owned by the thread executing the nested lock function - omp_init_nest_lock(), omp_set_nest_lock(), omp_unset_nest_lock(), omp_test_nest_lock(), omp_destroy_nest_lock()

Note: a thread always accesses the most recent copy of the lock, so you don't need to use a flush on the lock variable.

Synchronization: Simple Locks Protect resources with locks.

omp_lock_t lck; omp_init_lock(&lck); #pragma omp parallel private (tmp, id)

id = omp_get_thread_num(); tmp = do_lots_of_work(id); omp_set_lock(&lck); printf("%d %d", id, tmp); omp_unset_lock(&lck); Wait here for your turn.

Release the lock so the next thread gets a turn.

omp_destroy_lock(&lck);

Free-up storage when done.

Runtime Library routines

• Runtime environment routines:

- Modify/Check the number of threads
 - omp_set_num_threads(), omp_get_num_threads(), omp_get_thread_num(), omp_get_max_threads()
- Are we in an active parallel region?

- omp_in_parallel()

- Do you want the system to dynamically vary the number of threads from one parallel construct to another?
 - omp_set_dynamic, omp_get_dynamic();
- How many processors in the system?
 - omp_num_procs()

...plus a few less commonly used routines.

Runtime Library routines

To use a known, fixed number of threads in a program,
 (1) tell the system that you don't want dynamic adjustment of the number of threads, (2) set the number of threads, then (3) save the number you got.

Disable dynamic adjustment of the number of threads.

Request as many threads as you have processors.

omp_set_num_threads(omp_num_procs());

#pragma omp parallel
 { int id=omp_get_thread_num();
#pragma omp single

omp_set_dynamic(0);

#include <omp.h>

int num_threads;

void main()

Protect this op since Memory stores are not atomic

num_threads = omp_get_num_threads(); do_lots_of_stuff(id);

Even in this case, the system may give you fewer threads than requested. If the precise # of threads matters, test for it and respond accordingly.

Environment Variables

• Set the default number of threads to use. - OMP_NUM_THREADS int_literal

 Control how "omp for schedule(RUNTIME)" loop iterations are scheduled.

– OMP_SCHEDULE "schedule[, chunk_size]"

... Plus several less commonly used environment variables.

Outline

Introduction to OpenMP • Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

Data environment: Default storage attributes

- Shared Memory programming model:
 - Most variables are shared by default
- Global variables are SHARED among threads
 - Fortran: COMMON blocks, SAVE variables, MODULE variables
 - C: File scope variables, static
 - Both: dynamically allocated memory (ALLOCATE, malloc, new)
- But not everything is shared...
 - Stack variables in subprograms(Fortran) or functions(C) called from parallel regions are PRIVATE
 - Automatic variables within a statement block are PRIVATE.

Data sharing: Examples

double A[10]; int main() { int index[10]; #pragma omp parallel work(index); printf("%d\n", index[0]); extern double A[10]; void work(int *index) { double temp[10]; static int count;

A, index and count are shared by all threads.

temp is local to each thread



* Third party trademarks and names are the property of their respective owner.

Data sharing: Changing storage attributes

 One can selectively change storage attributes for constructs using the following clauses*

- SHARED
- PRIVATE
- FIRSTPRIVATE

All the clauses on this page apply to the OpenMP construct NOT to the entire region.

 The final value of a private inside a parallel loop can be transmitted to the shared variable outside the loop with:
 – LASTPRIVATE

 The default attributes can be overridden with:
 DEFAULT (PRIVATE | SHARED | NONE) DEFAULT(PRIVATE) is Fortran only

All data clauses apply to parallel constructs and worksharing constructs except "shared" which only applies to parallel constructs.

Data Sharing: Private Clause

- private(var) creates a new local copy of var for each thread.
 - The value is uninitialized
 - In OpenMP 2.5 the value of the shared variable is undefined after the region



Data Sharing: Private Clause When is the original variable valid?

- The original variable's value is unspecified in OpenMP 2.5.
- In OpenMP 3.0, if it is referenced outside of the construct
 - Implementations may reference the original variable or a copy A dangerous programming practice!

```
int tmp;
void danger() {
   tmp = 0;
#pragma omp parallel private(tmp)
   work();
   printf("%d\n", tmp);
}
tmp has unspecified
   value
```

extern int tmp; void work() { tmp = 5; } unspecified which copy of tmp

Data Sharing: Firstprivate Clause

• Firstprivate is a special case of private.

Initializes each private copy with the corresponding value from the master thread.



Data sharing: Lastprivate Clause

 Lastprivate passes the value of a private from the last iteration to a global variable.

```
void closer() {
    int tmp = 0;
#pragma omp parallel for firstprivate(tmp)
    lastprivate(tmp)
    for (int j = 0; j < 1000; ++j)
    tmp += j;
    printf("%d\n", tmp);
}
Each thread gets its own tmp
    with an initial value of 0

tmp is defined as its value at the "last
    sequential" iteration (i.e., for j=999)
53</pre>
```

Data Sharing: A data environment test

Consider this example of PRIVATE and FIRSTPRIVATE

variables A,B, and C = 1
#pragma omp parallel private(B) firstprivate(C)

- Are A,B,C local to each thread or shared inside the parallel region?
- What are their initial values inside and values after the parallel region?

Inside this parallel region ...

- "A" is shared by all threads; equals 1
- "B" and "C" are local to each thread.
 - B's initial value is undefined
 - C's initial value equals 1

Outside this parallel region ...

• The values of "B" and "C" are unspecified in OpenMP 2.5, and in OpenMP 3.0 if referenced in the region but outside the construct.

Data Sharing: Default Clause

- Note that the default storage attribute is DEFAULT(SHARED) (so no need to use it)
 - Exception: #pragma omp task
- To change default: **DEFAULT(PRIVATE)**
 - each variable in the construct is made private as if specified in a private clause
 - mostly saves typing
- DEFAULT(NONE): no default for variables in static extent. Must list storage attribute for each variable in static extent. Good programming practice!

Only the Fortran API supports default(private). <u>C/C++ only has default(shared</u>) or default(none).

Data Sharing: Default Clause Example

itotal = 1000 C\$OMP PARALLEL PRIVATE(np, each) np = omp_get_num_threads() each = itotal/np

C\$OMP END PARALLEL

.

These two code fragments are equivalent

itotal = 1000 C\$OMP PARALLEL DEFAULT(PRIVATE) SHARED(itotal) np = omp_get_num_threads() each = itotal/np

C\$OMP END PARALLEL

Data Sharing: tasks (OpenMP 3.0)

- The default for tasks is usually firstprivate, because the task may not be executed until later (and variables may have gone out of scope).
- Variables that are shared in all constructs starting from the innermost enclosing parallel construct are shared, because the barrier guarantees task completion.



Data sharing: Threadprivate

- Makes global data private to a thread
 - Fortran: COMMON blocks
 - C: File scope and static variables, static class members
- Different from making them **PRIVATE**
 - with **PRIVATE** global variables are masked.
 - THREADPRIVATE preserves global scope within each thread
- Threadprivate variables can be initialized using COPYIN or at time of definition (using languagedefined initialization capabilities).

A threadprivate example (C) Use threadprivate to create a counter for each thread.

```
int counter = 0;
#pragma omp threadprivate(counter)
int increment_counter()
{
    counter++;
    return (counter);
}
```

Data Copying: Copyin

You initialize threadprivate data using a copyin clause.

parameter (N=1000) common/buf/A(N) !\$OMP THREADPRIVATE(/buf/)

C Initialize the A array call init_data(N,A)

!\$OMP PARALLEL COPYIN(A)

... Now each thread sees threadprivate array A initialied ... to the global value set in the subroutine init_data()

!\$OMP END PARALLEL

end

Data Copying: Copyprivate

Used with a single region to broadcast values of privates from one member of a team to the rest of the team.

```
#include <omp.h>
void input_parameters (int, int); // fetch values of input parameters
void do_work(int, int);
```

```
void main()
```

```
int Nsize, choice;
```

```
#pragma omp parallel private (Nsize, choice)
{
```

```
#pragma omp single copyprivate (Nsize, choice)
input_parameters (Nsize, choice);
```

```
do_work(Nsize, choice);
```

Exercise 5: Monte Carlo Calculations

Using Random numbers to solve tough problems

- Sample a problem domain to estimate areas, compute probabilities, find optimal values, etc.
- Example: Computing π with a digital dart board:



N= 10
$$\pi = 2.8$$
N=100 $\pi = 3.16$ N= 1000 $\pi = 3.148$

- Throw darts at the circle/square.
- Chance of falling in circle is proportional to ratio of areas:

$$A_c = r^2 * \pi$$

 $A_s = (2*r) * (2*r) = 4 * \pi$
 $P = A_c/A_s = \pi / 4$

 Compute π by randomly choosing points, count the fraction that falls in the circle, compute pi.

Exercise 5

We provide three files for this exercise

• pi_mc.c: the monte carlo method pi program

- random.c: a simple random number generator
- random.h: include file for random number generator

Create a parallel version of this program without changing the interfaces to functions in random.c

This is an exercise in modular software ... why should a user of your parallel random number generator have to know any details of the generator or make any changes to how the generator is called?

• Extra Credit:

- Make the random number generator threadsafe.
- Make your random number generator numerically correct (nonoverlapping sequences of pseudo-random numbers).

Outline

Introduction to OpenMP Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

Sections worksharing Construct The Sections worksharing construct gives a different structured block to each thread.

#pragma omp parallel

#pragma omp sections

#pragma omp section
 X_calculation();
#pragma omp section
 y_calculation();
#pragma omp section
 z_calculation();

By default, there is a barrier at the end of the "omp sections". Use the "nowait" clause to turn off the barrier.

loop worksharing constructs: The schedule clause

The schedule clause affects how loop iterations are mapped onto threads

- schedule(static [,chunk])
 - Deal-out blocks of iterations of size "chunk" to each thread.
- schedule(dynamic[,chunk])
 - Each thread grabs "chunk" iterations off a queue until all iterations have been handled.
- schedule(guided[,chunk])
 - Threads dynamically grab blocks of iterations. The size of the block starts large and shrinks down to size "chunk" as the calculation proceeds.

schedule(runtime)

 Schedule and chunk size taken from the OMP_SCHEDULE environment variable (or the runtime library ... for OpenMP 3.0).

loop work-sharing constructs: The schedule clause

Schedule Clause	When To Use	Least work at runtime : scheduling done at compile-time
STATIC	Pre-determined and predictable by the programmer	
DYNAMIC	Unpredictable, highly variable work per iteration	Most work at runtime : complex scheduling logic used at run-time
GUIDED	Special case of dynamic to reduce scheduling overhead	

Exercise 6: hard

Consider the program linked.c

 Traverses a linked list computing a sequence of Fibonacci numbers at each node.

 Parallelize this program using constructs defined in OpenMP 2.5 (loop worksharing constructs).

Once you have a correct program, optimize it.

Exercise 6: easy

- Parallelize the matrix multiplication program in the file matmul.c
- Can you optimize the program by playing with how the loops are scheduled?

Outline

Introduction to OpenMP Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

OpenMP memory model

- OpenMP supports a shared memory model.
- All threads share an address space, but it can get complicated:



• A memory model is defined in terms of:

- Coherence: Behavior of the memory system when a single address is accessed by multiple threads.
- Consistency: Orderings of accesses to different addresses by multiple threads.

OpenMP Memory Model: Basic Terms


Consistency: Memory Access Re-ordering

• Re-ordering:

- Compiler re-orders program order to the code order
- Machine re-orders code order to the memory commit order
- At a given point in time, the temporary view of memory may vary from shared memory.
- Consistency models based on orderings of Reads (R), Writes (W) and Synchronizations (S):
 ♦R→R, W→W, R→W, R→S, S→S, W→S

Consistency

Sequential Consistency:

- In a multi-processor, ops (R, W, S) are sequentially consistent if:
 - They remain in program order for each processor.
 - They are seen to be in the same overall order by each of the other processors.
- Program order = code order = commit order

• Relaxed consistency:

Remove some of the ordering constraints for memory ops (R, W, S).

OpenMP and Relaxed Consistency

- OpenMP defines consistency as a variant of weak consistency:
 - S ops must be in sequential order across threads.
 - Can not reorder S ops with R or W ops on the same thread
 - Weak consistency guarantees

 $S \rightarrow W, S \rightarrow R, R \rightarrow S, W \rightarrow S, S \rightarrow S$

The Synchronization operation relevant to this discussion is flush.

Flush

 Defines a sequence point at which a thread is guaranteed to see a consistent view of memory with respect to the "flush set".

• The flush set is:

- "all thread visible variables" for a flush construct without an argument list.
- a list of variables when the "flush(list)" construct is used.
- The action of Flush is to guarantee that:
 - All R,W ops that overlap the flush set and occur prior to the flush complete before the flush executes
 - All R,W ops that overlap the flush set and occur after the flush don't execute until after the flush.
 - Flushes with overlapping flush sets can not be reordered.

Memory ops: R = Read, W = write, S = synchronization

Synchronization: flush example

 Flush forces data to be updated in memory so other threads see the most recent value

double A;

A = compute();

Note: OpenMP's flush is analogous to a fence in other shared memory API's.

Exercise 7: producer consumer

- Parallelize the "prod_cons.c" program.
- This is a well known pattern called the producer consumer pattern
 - One thread produces values that another thread consumes.
 - Often used with a stream of produced values to implement "pipeline parallelism"
- The key is to implement pairwise synchronization between threads.

Exercise 7: prod_cons.c

int main() double *A, sum, runtime; int flag = 0;A = (double *)malloc(N*sizeof(double)); runtime = omp_get_wtime(); fill_rand(N, A); // Producer: fill an array of data sum = Sum_array(N, A); // Consumer: sum the array runtime = omp_get_wtime() - runtime; printf(" In %If seconds, The sum is %If \n",runtime,sum);

I need to put the prod/cons pair inside a loop so its true pipeline parallelism.

> 79

What is the Big Deal with Flush?

- Compilers routinely reorder instructions implementing a program
 - This helps better exploit the functional units, keep machine busy, hide memory latencies, etc.
- Compiler generally cannot move instructions:
 - past a barrier
 - opast a flush on all variables
- But it can move them past a flush with a list of variables so long as those variables are not accessed
- Keeping track of consistency when flushes are used can be confusing ... especially if "flush(list)" is used.

Note: the flush operation does not actually synchronize different threads. It just ensures that a thread's values are made consistent with main memory.

Outline

Introduction to OpenMP Creating Threads Synchronization • Parallel Loops Synchronize single masters and stuff • Data environment Schedule your for and sections Memory model OpenMP 3.0 and Tasks

OpenMP pre-history

- OpenMP based upon SMP directive standardization efforts PCF and aborted ANSI X3H5 – late 80's
 - Nobody fully implemented either standard
 - Only a couple of partial implementations
- Vendors considered proprietary API's to be a competitive feature:
 - Every vendor had proprietary directives sets
 - Even KAP, a "portable" multi-platform parallelization tool used different directives on each platform

PCF – Parallel computing forum KAP – parallelization tool from KAI.



OpenMP Release History





Tasks

Adding tasking is the biggest addition for 3.0

Worked on by a separate subcommittee
 Ied by Jay Hoeflinger at Intel

Re-examined issue from ground up
 quite different from Intel taskq's



General task characteristics

A task has

- Code to execute
- A data environment (it owns its data)
- An assigned thread that executes the code and uses the data
- Two activities: packaging and execution
 - Each encountering thread packages a new instance of a task (code and data)
 - Some thread in the team executes the task at some later time

Definitions

- Task construct task directive plus structured block
- Task the package of code and instructions for allocating data created when a thread encounters a task construct
- Task region the dynamic sequence of instructions produced by the execution of a task by a thread



Tasks and OpenMP

- Tasks have been fully integrated into OpenMP
- Key concept: OpenMP has always had tasks, we just never called them that.
 - Thread encountering parallel construct packages up a set of *implicit* tasks, one per thread.
 - Team of threads is created.
 - Each thread in team is assigned to one of the tasks (and *tied* to it).
 - Barrier holds original master thread until all implicit tasks are finished.
- We have simply added a way to create a task explicitly for the team to execute.
- Every part of an OpenMP program is part of one task or another!



task Construct

#pragma omp task [clause[[,]clause] ...]
 structured-block

where clause can be one of:

```
if (expression)
untied
shared (list)
private (list)
firstprivate (list)
default( shared | none )
```



The if clause

• When the if clause argument is false

- The task is executed immediately by the encountering thread.
- The data environment is still local to the new task...
- ...and it's still a different task with respect to synchronization.

It's a user directed optimization

- when the cost of deferring the task is too great compared to the cost of executing the task code
- to control cache and memory affinity

When/where are tasks complete?

At thread barriers, explicit or implicit

- applies to all tasks generated in the current parallel region up to the barrier
- matches user expectation

• At task barriers

 i.e. Wait until all tasks defined in the current task have completed.

#pragma omp taskwait

 Note: applies only to tasks generated in the current task, not to "descendants".

OpenMP 3.0

Example – parallel pointer chasing using tasks

```
#pragma omp parallel
ł
  #pragma omp single private(p)
    p = listhead ;
                            p is firstprivate inside
                            this task
    while (p) {
        #pragma omp task
                 process (p)
        p=next (p) ;
      }
```

<u>OpenMP 3.0</u>

Example – parallel pointer chasing on multiple lists using tasks

```
#pragma omp parallel
{
   #pragma omp for private(p)
   for ( int i =0; i <numlists ; i++) {</pre>
       p = listheads [ i ] ;
       while (p ) {
       #pragma omp task
           process (p)
       p=next (p ) ;
```

OpenMP 3.0

Example: postorder tree traversal

void postorder(node *p) {
 if (p->left)
 #pragma omp task
 postorder(p->left);
 if (p->right)
 #pragma omp task
 postorder(p->right);
#pragma omp taskwait // wait for descendants
 process(p->data);
 Task scheduling point

• Parent task suspended until children tasks complete



Task switching

- Certain constructs have task scheduling points at defined locations within them
- When a thread encounters a task scheduling point, it is allowed to suspend the current task and execute another (called *task switching*)
- It can then return to the original task and resume



Task switching example

```
#pragma omp single
{
  for (i=0; i<ONEZILLION; i++)
    #pragma omp task
    process(item[i]);
}</pre>
```

- Too many tasks generated in an eye-blink
- Generating task will have to suspend for a while
- With task switching, the executing thread can:
 - execute an already generated task (draining the
 "task pool")

dive into the encountered task (could be very cache-friendly)



Thread switching

```
#pragma omp single
{
    #pragma omp task untied
    for (i=0; i<ONEZILLION; i++)
        #pragma omp task
        process(item[i]);
}</pre>
```

- Eventually, too many tasks are generated
- Generating task is suspended and executing thread switches to a long and boring task
- Other threads get rid of all already generated tasks, and start starving...
- With thread switching, the generating task can be resumed by a different thread, and starvation is over
- Too strange to be the default: the programmer is responsible!



Dealing with taskprivate data

The Taskprivate directive was removed from OpenMP 3.0
Too expensive to implement
Restrictions on task scheduling allow threadprivate data to be used
User can avoid thread switching with tied tasks

Task scheduling points are well defined



Conclusions on tasks

- Enormous amount of work by many people
- Tightly integrated into 3.0 spec
- Flexible model for irregular parallelism
- Provides balanced solution despite often conflicting goals
- Appears that performance can be reasonable

Nested parallelism

 Better support for nested parallelism • Per-thread internal control variables Allows, for example, calling omp_set_num_threads() inside a parallel region. Controls the team sizes for next level of parallelism Library routines to determine depth of nesting, IDs of parent/grandparent etc. threads, team sizes of parent/grandparent etc. teams omp get active level() omp_get_ancestor(level) omp_get_teamsize(level)



Parallel loops

 Guarantee that this works ... i.e. that the same schedule is used in the two loops:

```
!$omp do schedule(static)
do i=1,n
        a(i) = ....
end do
!$omp end do nowait
!$omp do schedule(static)
do i=1,n
        .... = a(i)
end do
```



Loops (cont.)

Allow collapsing of perfectly nested loops

```
!$omp parallel do collapse(2)
do i=1,n
    do j=1,n
    end do
end do
```

Will form a single loop and then parallelize that



Loops (cont.)

Made schedule(runtime) more useful
 can get/set it with library routines
 _omp_set_schedule()

omp_get_schedule()

allow implementations to implement their own schedule kinds

 Added a new schedule kind AUTO which gives full freedom to the runtime to determine the scheduling of iterations to threads.

 Allowed C++ Random access iterators as loop control variables in parallel loops



Portable control of threads

 Added environment variable to control the size of child threads' stack

OMP_STACKSIZE

 Added environment variable to hint to runtime how to treat idle threads

OMP_WAIT_POLICY

ACTIVE keep threads alive at barriers/locks

PASSIVE try to release processor at barriers/locks



Control program execution

• Added environment variable and runtime routines to get/set the maximum number of active levels of nested parallelism OMP MAX ACTIVE LEVELS omp set max active levels() omp_get_max_active_levels() • Added environment variable to set maximum number of threads in use **OMP_THREAD_LIMIT** omp_get_thread_limit()



Odds and ends

- Allow unsigned ints in parallel for loops
- Disallow use of the original variable as master thread's private variable
- Make it clearer where/how private objects are constructed/destructed
- Relax some restrictions on allocatable arrays and Fortran pointers
- Plug some minor gaps in memory model
- Allow C++ static class members to be threadprivate
- Improve C/C++ grammar
- Minor fixes and clarifications to 2.5

Exercise 8: tasks in OpenMP

Consider the program linked.c
Traverses a linked list computing a sequence of Fibonacci numbers at each node.
Parallelize this program using tasks.
Compare your solution's complexity compared to the approach without tasks.

Conclusion

- OpenMP 3.0 is a major upgrade ... expands the range of algorithms accessible from OpenMP.
- OpenMP is fun and about "as easy as we can make it" for applications programmers working with shared memory platforms.
OpenMP Organizations

 OpenMP architecture review board URL, the "owner" of the OpenMP specification: www.openmp.org
 OpenMP User's Group (cOMPunity) URL: www.compunity.org

Get involved, join compunity and help define the future of OpenMP

Books about OpenMP



Using OpenMP

PORTABLE SHARED MEMORY PARALLEL PROGRAMMING

BARBARA CHAPMAN, GABRIELE JOST, AND RUUD VAN DER PAS foreword by DAVID J. KUCK

 A new book about OpenMP 2.5 by a team of authors at the forefront of OpenMP's evolution.

PATTERNS FOR PARALLEL PROGRAMMING



SOFTWARE PATTERNS SERIES

 A book about how to "think parallel" with examples in OpenMP, MPI and java

OpenMP Papers

- Sosa CP, Scalmani C, Gomperts R, Frisch MJ. Ab initio quantum chemistry on a ccNUMA architecture using OpenMP. III. Parallel Computing, vol.26, no.7-8, July 2000, pp.843-56. Publisher: Elsevier, Netherlands.
- Couturier R, Chipot C. Parallel molecular dynamics using OPENMP on a shared memory machine. Computer Physics Communications, vol.124, no.1, Jan. 2000, pp.49-59. Publisher: Elsevier, Netherlands.
- Bentz J., Kendall R., "Parallelization of General Matrix Multiply Routines Using OpenMP", Shared Memory Parallel Programming with OpenMP, Lecture notes in Computer Science, Vol. 3349, P. 1, 2005
- Bova SW, Breshearsz CP, Cuicchi CE, Demirbilek Z, Gabb HA. Dual-level parallel analysis of harbor wave response using MPI and OpenMP. International Journal of High Performance Computing Applications, vol.14, no.1, Spring 2000, pp.49-64. Publisher: Sage Science Press, USA.
- Ayguade E, Martorell X, Labarta J, Gonzalez M, Navarro N. Exploiting multiple levels of parallelism in OpenMP: a case study. Proceedings of the 1999 International Conference on Parallel Processing. IEEE Comput. Soc. 1999, pp.172-80. Los Alamitos, CA, USA.
- Bova SW, Breshears CP, Cuicchi C, Demirbilek Z, Gabb H. Nesting OpenMP in an MPI application. Proceedings of the ISCA 12th International Conference. Parallel and Distributed Systems. ISCA. 1999, pp.566-71. Cary, NC, USA.

OpenMP Papers (continued)

- Jost G., Labarta J., Gimenez J., What Multilevel Parallel Programs do when you are not watching: a Performance analysis case study comparing MPI/OpenMP, MLP, and Nested OpenMP, Shared Memory Parallel Programming with OpenMP, Lecture notes in Computer Science, Vol. 3349, P. 29, 2005
- Gonzalez M, Serra A, Martorell X, Oliver J, Ayguade E, Labarta J, Navarro N. Applying interposition techniques for performance analysis of OPENMP parallel applications. Proceedings 14th International Parallel and Distributed Processing Symposium. IPDPS 2000. IEEE Comput. Soc. 2000, pp.235-40.
- Chapman B, Mehrotra P, Zima H. Enhancing OpenMP with features for locality control. Proceedings of Eighth ECMWF Workshop on the Use of Parallel Processors in Meteorology. Towards Teracomputing. World Scientific Publishing. 1999, pp.301-13. Singapore.
- Steve W. Bova, Clay P. Breshears, Henry Gabb, Rudolf Eigenmann, Greg Gaertner, Bob Kuhn, Bill Magro, Stefano Salvini. Parallel Programming with Message Passing and Directives; SIAM News, Volume 32, No 9, Nov. 1999.
- Cappello F, Richard O, Etiemble D. Performance of the NAS benchmarks on a cluster of SMP PCs using a parallelization of the MPI programs with OpenMP. Lecture Notes in Computer Science Vol.1662. Springer-Verlag. 1999, pp.339-50.
- Liu Z., Huang L., Chapman B., Weng T., Efficient Implementationi of OpenMP for Clusters with Implicit Data Distribution, Shared Memory Parallel Programming with OpenMP, Lecture notes in Computer Science, Vol. 3349, P. 121, 2005

OpenMP Papers (continued)

- B. Chapman, F. Bregier, A. Patil, A. Prabhakar, "Achieving performance under OpenMP on ccNUMA and software distributed shared memory systems," *Concurrency and Computation: Practice and Experience.* 14(8-9): 713-739, 2002.
- J. M. Bull and M. E. Kambites. JOMP: an OpenMP-like interface for Java. Proceedings of the ACM 2000 conference on Java Grande, 2000, Pages 44 - 53.
- L. Adhianto and B. Chapman, "Performance modeling of communication and computation in hybrid MPI and OpenMP applications, Simulation Modeling Practice and Theory, vol 15, p. 481-491, 2007.
- Shah S, Haab G, Petersen P, Throop J. Flexible control structures for parallelism in OpenMP; Concurrency: Practice and Experience, 2000; 12:1219-1239. Publisher John Wiley & Sons, Ltd.
- Mattson, T.G., How Good is OpenMP? Scientific Programming, Vol. 11, Number 2, p.81-93, 2003.
- Duran A., Silvera R., Corbalan J., Labarta J., "Runtime Adjustment of Parallel Nested Loops", Shared Memory Parallel Programming with OpenMP, Lecture notes in Computer Science, Vol. 3349, P. 137, 2005

- Exercise 1: hello world
 - Exercise 2: Simple SPMD Pi program
 - Exercise 3: SPMD Pi without false sharing
 - Exercise 4: Loop level Pi
 - Exercise 5: Producer-consumer
 - Exercise 6: Monte Carlo Pi and random numbers
 - Exercise 7: hard, linked lists without tasks
 - Exercise 7: easy, matrix multiplication
 - Exercise 8: linked lists with tasks

Exercise 1: Solution A multi-threaded "Hello world" program

Write a multithreaded program where each thread prints "hello world".



- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
 - Exercise 3: SPMD Pi without false sharing
 - Exercise 4: Loop level Pi
 - Exercise 5: Producer-consumer
 - Exercise 6: Monte Carlo Pi and random numbers
 - Exercise 7: hard, linked lists without tasks
 - Exercise 7: easy, matrix multiplication
 - Exercise 8: linked lists with tasks

The SPMD pattern

- The most common approach for parallel algorithms is the SPMD or <u>Single Program</u> <u>Multiple Data pattern.</u>
- Each thread runs the same program (Single Program), but using the thread ID, they operate on different data (Multiple Data) or take slightly different paths through the code.
- In OpenMP this means:
 - A parallel region "near the top of the code".
 - Pick up thread ID and num_threads.
 - Use them to split up loops and select different blocks of data to work on.

Exercise 2: A simple SPMD pi program

```
Promote scalar to an
#include <omp.h>
                                                            array dimensioned by
                                         double step;
static long num_steps = 100000;
                                                            number of threads to
#define NUM_THREADS 2
                                                            avoid race condition.
void main ()
          int i, nthreads; double pi, sum[NUM_THREADS];
          step = 1.0/(double) num_steps;
          omp_set_num_threads(NUM_THREADS);
  #pragma omp parallel
                                                    Only one thread should copy
         int i, id, nthrds;
                                                    the number of threads to the
         double x:
                                                    global value to make sure
                                                    multiple threads writing to the
         id = omp_get_thread_num();
                                                    same address don't conflict.
         nthrds = omp_get_num_threads();
         if (id == 0) nthreads = nthrds;
          for (i=id, sum[id]=0.0;i< num_steps; i=i+nthrds) {</pre>
                  x = (i+0.5)^*step;
                                                         This is a common trick in
                  sum[id] += 4.0/(1.0+x^*x);
                                                         SPMD programs to create
                                                         a cyclic distribution of loop
                                                         iterations
          for(i=0, pi=0.0;i<nthreads;i++)pi += sum[i] * step;
                                                                         118 🔰
```

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
 - Exercise 4: Loop level Pi
 - Exercise 5: Producer-consumer
 - Exercise 6: Monte Carlo Pi and random numbers
 - Exercise 7: hard, linked lists without tasks
 - Exercise 7: easy, matrix multiplication
 - Exercise 8: linked lists with tasks

False sharing

 If independent data elements happen to sit on the same cache line, each update will cause the cache lines to "slosh back and forth" between threads.

This is called "false sharing".

 If you promote scalars to an array to support creation of an SPMD program, the array elements are contiguous in memory and hence share cache lines.

Result ... poor scalability

Solution:

- When updates to an item are frequent, work with local copies of data instead of an array indexed by the thread ID.
- Pad arrays so elements you use are on distinct cache lines.

Exercise 3: SPMD Pi without false sharing



- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
 - Exercise 5: Producer-consumer
 - Exercise 6: Monte Carlo Pi and random numbers
 - Exercise 7: hard, linked lists without tasks
 - Exercise 7: easy, matrix multiplication
 - Exercise 8: linked lists with tasks

Exercise 4: solution

#include <omp.h> static long num_steps = 100000; double step; #define NUM_THREADS 2 For good OpenMP void main () implementations, reduction is more int i; double x, pi, sum = 0.0; scalable than critical. step = 1.0/(double) num_steps; omp_set_num_threads(NUM_THREADS); #pragma omp parallel for private(x) reduction(+:sum) for_(i=0;i< num_steps; i++){</pre> x = (i+0.5)*step; i private sum = sum + 4.0/(1.0+x*x);by default Note: we created a parallel pi = step * sum; program without changing any code and by adding 4 simple lines!

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
- Exercise 5: Monte Carlo Pi and random numbers
 - Exercise 6: hard, linked lists without tasks
 - Exercise 6: easy, matrix multiplication
 - Exercise 7: Producer-consumer
 - Exercise 8: linked lists with tasks

Computers and random numbers

- We use "dice" to make random numbers:
 - Given previous values, you cannot predict the next value.
 - There are no patterns in the series ... and it goes on forever.
- Computers are deterministic machines ... set an initial state, run a sequence of predefined instructions, and you get a deterministic answer
 - By design, computers are not random and cannot produce random numbers.
- However, with some very clever programming, we can make "pseudo random" numbers that are as random as you need them to be ... but only if you are very careful.
- Why do I care? Random numbers drive statistical methods used in countless applications:
 - Sample a large space of alternatives to find statistically good answers (Monte Carlo methods).

Monte Carlo Calculations: Using Random numbers to solve tough problems

- Sample a problem domain to estimate areas, compute probabilities, find optimal values, etc.
- Example: Computing π with a digital dart board:



N= 10
$$\pi$$
 = 2.8N=100 π = 3.16N= 1000 π = 3.148

- Throw darts at the circle/square.
- Chance of falling in circle is proportional to ratio of areas:

$$A_c = r^2 * \pi$$

 $A_s = (2*r) * (2*r) = 4 * \pi$
 $P = A_c/A_s = \pi / 4$

 Compute π by randomly choosing points, count the fraction that falls in the circle, compute pi.

Parallel Programmers love Monte Carlo algorithms Embarrassingly parallel: the parallelism is so easy its

```
#include "omp.h"
                                                  embarrassing.
static long num_trials = 10000;
                                         Add two lines and you have a
int main ()
                                                parallel program.
 long i; long Ncirc = 0; double pi, x, y;
 double r = 1.0; // radius of circle. Side of squrare is 2*r
 seed(0,-r, r); // The circle and square are centered at the origin
 #pragma omp parallel for private (x, y) reduction (+:Ncirc)
 for(i=0;i<num_trials; i++)</pre>
   x = random(); y = random();
   }
```

```
pi = 4.0 * ((double)Ncirc/(double)num_trials);
printf("\n %d trials, pi is %f \n",num_trials, pi);
```

127

Linear Congruential Generator (LCG)

LCG: Easy to write, cheap to compute, portable, OK quality

random_next = (MULTIPLIER * random_last + ADDEND)% PMOD; random_last = random_next;

- If you pick the multiplier and addend correctly, LCG has a period of PMOD.
- Picking good LCG parameters is complicated, so look it up (Numerical Recipes is a good source). I used the following:
 - MULTIPLIER = 1366
 - ADDEND = 150889
 - ♦ PMOD = 714025

LCG code

static long MULTIPLIER = 1366; static long ADDEND = 150889; static long PMOD = 714025; long random_last = 0; double random ()

Seed the pseudo random sequence by setting random_last

```
long random_next;
```

random_next = (MULTIPLIER * random_last + ADDEND)% PMOD; random_last = random_next;

```
return ((double)random_next/(double)PMOD);
```

Running the PI_MC program with LCG generator



Program written using the Intel C/C++ compiler (10.0.659.2005) in Microsoft Visual studio 2005 (8.0.50727.42) and running on a dual-core laptop (Intel T2400 @ 1.83 Ghz with 2 GB RAM) running Microsoft Windows XP. 130

LCG code: threadsafe version

```
static long MULTIPLIER = 1366;
static long ADDEND = 150889;
static long PMOD = 714025;
long random_last = 0;
#pragma omp threadprivate(random_last)
double random ()
```

```
long random_next;
```

}

random_last carries state between random number computations,

To make the generator threadsafe, make random_last threadprivate so each thread has its own copy.

```
random_next = (MULTIPLIER * random_last + ADDEND)% PMOD;
random_last = random_next;
```

```
return ((double)random_next/(double)PMOD);
```

Thread safe random number generators

Log₁₀ number of samples



Thread safe version gives the same answer each time you run the program.

But for large number of samples, its quality is lower than the one thread result!

Why?

Pseudo Random Sequences	5
 Random number Generators (RNGs) define a sequence numbers of length equal to the period of the RNG 	e of pseudo-random
 In a typical problem, you grab a subsequence of the F 	RNG range
Seed determines starting point	
 Grab arbitrary seeds and you may generate overlapping 	g sequences
E.g. three sequences last one wraps at the end of the R	RNG period.
Thread 1 Thread 2	

quality or even wrong answers!

133

Parallel random number generators

- Multiple threads cooperate to generate and use random numbers.
- Solutions:
 - Replicate and Pray
 - Give each thread a separate, independent generator
 - Have one thread generate all the numbers.
 - Leapfrog ... deal out sequence values "round robin" as if dealing a deck of cards.
 - Block method ... pick your seed so each threads gets a distinct contiguous block.
- Other than "replicate and pray", these are difficult to implement. Be smart ... buy a math library that does it right.

If done right, can generate the same sequence regardless of the number of threads ...

Nice for debugging, but not really needed scientifically.

Intel's Math kernel Library supports all of these methods.

MKL Random number generators (RNG)

• MKL includes several families of RNGs in its vector statistics library.

Specialized to efficiently generate vectors of random numbers

#define BLOCK 100 double buff[BLOCK]; Select type of VSLStreamStatePtr stream; **RNG** and set seed Initialize a stream or vslNewStream(&ran_stream, VSL_BRNG_WH, (int)seed_val); pseudo random vdRngUniform (VSL_METHOD_DUNIFORM_STD, stream, numbers **BLOCK**, buff, low, hi) vsIDeleteStream(&stream); Fill buff with BLOCK pseudo rand. nums, uniformly distributed with values between lo and hi. Delete the stream when you are done

Wichmann-Hill generators (WH)

- WH is a family of 273 parameter sets each defining a nonoverlapping and independent RNG.
- Easy to use, just make each stream threadprivate and initiate RNG stream so each thread gets a unique WG RNG.

VSLStreamStatePtr stream;

#pragma omp threadprivate(stream)

. . .

vsINewStream(&ran_stream, VSL_BRNG_WH+Thrd_ID, (int)seed);

Independent Generator for each thread

Log₁₀ number of samples



Notice that once you get beyond the high error, small sample count range, adding threads doesn't decrease quality of random sampling.

Log₁₀ Relative error

Leap Frog method

- Interleave samples in the sequence of pseudo random numbers:
 - Thread i starts at the ith number in the sequence
 - Stride through sequence, stride length = number of threads.
- Result ... the same sequence of values regardless of the number of threads.

```
#pragma omp single
  nthreads = omp_get_num_threads();
   iseed = PMOD/MULTIPLIER; // just pick a seed
                                                         One thread
   pseed[0] = iseed;
                                                         computes offsets
  mult_n = MULTIPLIER;
                                                         and strided
                                                         multiplier
  for (i = 1; i < nthreads; ++i)
    iseed = (unsigned long long)((MULTIPLIER * iseed) % PMOD);
    pseed[i] = iseed;
                                                    LCG with Addend = 0
    mult_n = (mult_n * MULTIPLIER) % PMOD;
                                                    just to keep things
                                                    simple
                                                  Each thread stores offset
                                                  starting point into its
random_last = (unsigned long long) pseed[id];
                                                  threadprivate "last random"
                                                  value
```

Same sequence with many threads.

 We can use the leapfrog method to generate the same answer for any number of threads

One thread	2 threads	4 threads
3.156	3.156	3.156
3.1168	3.1168	3.1168
3 13964	3 13964	3.13964
		3.140348
		3.141658
		3.1563.1563.11683.11683.139643.139643.1403483.140348

Used the MKL library with two generator streams per computation: one for the x values (WH) and one for the y values (WH+1). Also used the leapfrog method to deal out iterations among threads.

139

Ú

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
- Exercise 5: Monte Carlo Pi and random numbers
- Exercise 6: hard, linked lists without tasks
 - Exercise 6: easy, matrix multiplication
 - Exercise 7: Producer-consumer
 - Exercise 8: linked lists with tasks

Linked lists without tasks See the file Linked_omp25.c while (p != NULL) { p = p - next;Count number of items in the linked list count++; p = head;for(i=0; i<count; i++) { parr[i] = p;Copy pointer to each node into an array p = p - next;**#pragma omp parallel** #pragma omp for schedule(static,1) for(i=0; i<count; i++)</pre> Process nodes in parallel with a for loop processwork(parr[i]); } **Default schedule** Static,1 **One Thread** 48 seconds 45 seconds Two Threads 39 seconds 28 seconds Results on an Intel dual core 1.83 GHz CPU, Intel IA-32 compiler 10.1 build 2

Linked lists without tasks: C++ STL

See the file Linked_cpp.cpp

std::vector<node *> nodelist;
for (p = head; p != NULL; p = p->next)
nodelist.push_back(p); Copy p

Copy pointer to each node into an array

Count number of items in the linked list

Process nodes in parallel with a for loop

	C++, default sched.	C++, (static,1)	C, (static,1)	
One Thread	37 seconds	49 seconds	45 seconds	
Two Threads	47 seconds	32 seconds	28 seconds	
142 U				

Results on an Intel dual core 1.83 GHz CPU, Intel IA-32 compiler 10.1 build

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
- Exercise 5: Monte Carlo Pi and random numbers
- Exercise 6: hard, linked lists without tasks
- Exercise 6: easy, matrix multiplication
 - Exercise 7: Producer-consumer
 - Exercise 8: linked lists with tasks

Matrix multiplication

```
#pragma omp parallel for private(tmp, i, j, k)
for (i=0; i<Ndim; i++){
    for (j=0; j<Mdim; j++){
        tmp = 0.0;
        for(k=0;k<Pdim;k++){
            /* C(i,j) = sum(over k) A(i,k) * B(k,j) */
            tmp += *(A+(i*Ndim+k)) * *(B+(k*Pdim+j));
        }
        *(C+(i*Ndim+j)) = tmp;
}</pre>
```

•On a dual core laptop

}

•13.2 seconds 153 Mflops one thread

•7.5 seconds 270 Mflops two threads

U

144

Results on an Intel dual core 1.83 GHz CPU, Intel IA-32 compiler 10.1 build 2

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
- Exercise 5: Monte Carlo Pi and random numbers
- Exercise 6: hard, linked lists without tasks
- Exercise 6: easy, matrix multiplication
- Exercise 7: Producer-consumer
 - Exercise 8: linked lists with tasks

Pair wise synchronizaion in OpenMP

- OpenMP lacks synchronization constructs that work between pairs of threads.
- When this is needed you have to build it yourself.
- Pair wise synchronization
 - Use a shared flag variable
 - Reader spins waiting for the new flag value
 - Use flushes to force updates to and from memory

Exercise 7: producer consumer

int main()

```
double *A, sum, runtime; int numthreads, flag = 0;
A = (double *)malloc(N*sizeof(double));
```

```
#pragma omp parallel sections
```

```
#pragma omp section
{
   fill_rand(N, A);
   #pragma omp flush
   flag = 1;
   #pragma omp flush (flag)
}
#pragma omp section
```

```
#pragma omp flush (flag)
while (flag != 1){
    #pragma omp flush (flag)
}
#pragma omp flush
```

```
sum = Sum_array(N, A);
```

Use flag to Signal when the "produced" value is ready

Flush forces refresh to memory. Guarantees that the other thread sees the new value of A

Flush needed on both "reader" and "writer" sides of the communication

Notice you must put the flush inside the while loop to make sure the updated flag variable is seen

- Exercise 1: hello world
- Exercise 2: Simple SPMD Pi program
- Exercise 3: SPMD Pi without false sharing
- Exercise 4: Loop level Pi
- Exercise 5: Monte Carlo Pi and random numbers
- Exercise 6: hard, linked lists without tasks
- Exercise 6: easy, matrix multiplication
- Exercise 7: Producer-consumer
- Exercise 8: linked lists with tasks

```
Linked lists with tasks (intel taskq)
 See the file Linked_intel_taskq.c
#pragma omp parallel
ł
  #pragma intel omp taskq
   while (p != NULL) {
       #pragma intel omp task captureprivate(p)
        processwork(p);
       p = p - next;
                         Array, Static, 1
                                         Intel taskq
            One Thread
                         45 seconds
                                         48 seconds
            Two Threads
                         28 seconds
                                         30 seconds
                                                         149
```

Results on an Intel dual core 1.83 GHz CPU, Intel IA-32 compiler 10.1 build 2

Linked lists with tasks (OpenMP 3)

See the file Linked_intel_taskq.c

#pragma omp parallel

#pragma omp single

```
p=head;
while (p) {
  #pragma omp task firstprivate(p)
     processwork(p);
     p = p->next;
```

Creates a task with its own copy of "p" initialized to the value of "p" when the task is defined

150

Compiler notes: Intel on Windows

Intel compiler:

- Launch SW dev environment ... on my laptop I use:
 - start/intel software development tools/intel C++ compiler 10.1/C+ build environment for 32 bit apps
- •cd to the directory that holds your source code
- Build software for program foo.c

-icl /Qopenmp foo.c

- Set number of threads environment variable
 - -set OMP_NUM_THREADS=4
- Run your program
 - -foo.exe

To get rid of the pwd on the prompt, type

prompt = %

Compiler notes: Visual Studio

Start "new project"

Select win 32 console project

- Set name and path
- On the next panel, Click "next" instead of finish so you can select an empty project on the following panel.
- Drag and drop your source file into the source folder on the visual studio solution explorer
- Activate OpenMP
 - Go to project properties/configuration properties/C.C++/language ... and activate OpenMP
- Set number of threads inside the program
- Build the project
- Run "without debug" from the debug menu.

Notes from the SC08 tutorial

- It seemed to go very well. We had over 50 people who stuck it out throughout the day.
- Most people brought their laptops (only 7 loaner laptops were used). And of those with laptops, most had preloaded an OS.
- The chaos at the beginning was much less than I expected. I had fears of an hour or longer to get everyone setup. But thanks to PGI providing a license key in a temp file, we were able to get everyone installed in short order.
- Having a team of 4 (two speakers and two assistants) worked well. It would have been messier without a hardcore compiler person such as Larry. With dozens of different configurations, he had to do some serious trouble-shooting to get the most difficult cases up and running.
- The exercises used early in the course were good. The ones after lunch were too hard. I need to refine the exercise set. One idea is to for each slot have an "easy" exercise and a "hard" exercise. This will help me keep the group's experience more balanced.
- Most people didn't get the threadprivate exercise. The few people who tried the linked-list exercise were amazingly creative ... one even gettting a single/nowait version to work.